OWNER'S MANUAL

BLUE GENIUS™ TOUCH CONTROL MASTER CONTROL PANELS



ACTUAL PRODUCT MAY NOT APPEAR EXACTLY AS SHOWN

AWARNING

Do not operate or service this product unless you have read and fully understand the entire contents of this manual. Failure to do so may result in bodily injury or death.





Table of Contents

1.0 1.1	ABOUT BLUE GENIUS™ TOUCH CONTROL MASTER CONTROL PANELS OWNER'S PURCHASE RECORD	5 5
2.0	INTRODUCTION	7
2.1	WARRANTY INFORMATION	7
2.2	EXCLUSION OF LIABILITY	7
2.3	MANUFACTURER'S NOTE	8
2.4	OWNER'S RESPONSIBILITY	8
3.0	SAFETY MESSAGE COLOR IDENTIFICATION	9
3.1	OPERATIONAL SAFETY WARNINGS	9
4.0	LOCKOUT / TAGOUT PROCEDURE AND RULES	10
4.1	ROTARY DISCONNECT: PLATINUM SERIES	10
5.0	CONTROL PANEL OPERATION: GOLD SERIES III	11
5.1	BUTTON FUNCTION: GOLD SERIES III	11
5.2	CONTROL SECTIONS: GOLD SERIES III	12
6.0	RECOMMENDED SPARE PARTS: GOLD SERIES III	13
7.0	EQUIPMENT COMPONENT ILLUSTRATIONS: GOLD SERIES III	14
7.1	COMPONENTS AS SHIPPED CHECK LIST: GOLD SERIES III	14
7.2	MECHANICAL ASSEMBLY: GOLD SERIES III	15
7.3	GENERAL DIMENSIONS: GOLD SERIES III	17
8.0	CONTROL PANEL OPERATION: PLATINUM SERIES	18
8.1	BUTTON FUNCTION: PLATINUM SERIES	18
8.2	CONTROL SECTIONS: PLATINUM SERIES	19
9.0	RECOMMENDED SPARE PARTS: PLATINUM SERIES	21
10.0	EQUIPMENT COMPONENT ILLUSTRATIONS: PLATINUM SERIES	22
10.1	COMPONENTS AS SHIPPED CHECK LIST: PLATINUM SERIES	22
10.2	MECHANICAL ASSEMBLY: PLATINUM SERIES	23
10.3	GENERAL DIMENSIONS: PLATINUM SERIES	26
11.0	DECAL IDENTIFICATION AND LOCATION: GOLD SERIES III AND PLATINUM SERIES	27
12.0	STOP PROCEDURE: GOLD SERIES III AND PLATINUM SERIES	28
13.0	OPERATING INSTRUCTIONS: GOLD SERIES III AND PLATINUM SERIES	29
13.1	ALTERNATIVE METHODS OF OPERATION: GOLD SERIES III AND PLATINUM SERIES	31
14.0	ENGAGING THE OVERRIDE FEATURE: GOLD SERIES III AND PLATINUM SERIES	32
14.1	RELEASING THE OVERRIDE FEATURE: GOLD SERIES III AND PLATINUM SERIES	33
15.0	EXTERIOR TRAFFIC LIGHT / MIRROR SIGN IMAGE: GOLD SERIES III AND PLATINUM SERIES	34
16.0	CONTROL PANEL LCD MESSAGES: GOLD SERIES III AND PLATINUM SERIES	35
17.0	WIRING DIAGRAMS: GOLD SERIES III AND PLATINUM SERIES	36
17.1	WIRING DIAGRAM—115V SINGLE PHASE: GOLD SERIES III (SVR303 & FH COMBO)	36
17.2	WIRING DIAGRAM—230V SINGLE PHASE: GOLD SERIES III (TL85 REMOTE & FH COMBO)	37
17.3	POWER WIRING DIAGRAM - 230-575V THREE PHASE: PLATINUM SERIES* (SVR303 & VL COMBO)	38
17.4	CONTROL WIRING DIAGRAM - 230-575V THREE PHASE:PLATINUM SERIES (SVR303 & VL COMBO)	40



1.0 ABOUT BLUE GENIUS™ TOUCH CONTROL MASTER CONTROL PANELS

Blue Genius™ Touch Control Master Control Panels (MCP) represent the highest level in loading dock safety and productivity.

The Master Control Panels consolidate the controls for multiple interconnected dock devices:

- Docker Leveler
- Vehicle Restraint
- Overhead door (standard with Platinum Series, option with Gold Series III)
- Inflatable Seal (standard with Platinum Series, option with Gold Series III)
- Dock Lights (standard with Platinum Series, option with Gold Series III)
- Communications Traffic Lights (trailer and forklift) and LCD menu screen

LEGEND
Section applies only to Blue Genius™ Gold Series III
Section applies only to Blue Genius™ Platinum Series
Section applies to both Blue Genius™ control panels

The equipment operation sequence is structured to ensure safety and efficiency. The LCD menu screen provides ongoing equipment status as well as instructions for operating and troubleshooting. The interior and exterior LED light communication system displays safety signals to truck drivers and dock personnel. The rotary disconnect (Platinum Series only) cuts power to the unit for routine servicing and maintenance.


The panel's NEMA4X-rated polycarbonate enclosure is wet and corrosion-resistant, ensuring seamless operation in the wash-down zone and outdoor locations. The control panels are also compatible with operations that must adhere to the FDA's high cleaning standards, such as pharmaceutical and chemical handling locations.

1.1 OWNER'S PURCHASE RECORD

OWNER'S PURCHASE RECORD Please record information for future inquiries and to validate warranty. (See Section "2.1 WARRANTY INFORMATION" on page 7 for warranty validation)						
Dealer:	Date in Service:					
	Number of Units:					
Gold Series III Platinum Series						
Serial Number:	Door #:					
Serial Number:	Door #:					
Serial Number:	Door #:					
Serial Number:	Door #:					

The manufacturer offers a full line of dock levelers, dock safety equipment, accessories, ergonomic and scissor lift equipment, seals and shelters, and industrial trucks. Concurrent with a continuing product improvement program, specifications are subject to change without notice (see "2.2 EXCLUSION OF LIABILITY" on page 7 of this manual). Please contact the manufacturer for latest information. Some features illustrated may be optional in certain market areas.

See Section "11.0 Decal Identification and Location: Gold Series III and Platinum Series" on page 27 item #3 for serial number location.



2.0 INTRODUCTION

The following is a quick reference to important procedures that must be followed while using the MCP. It is not intended to cover, or suggest that it does cover, all procedures necessary to ensure safe operation. All operators should be aware of and abide by all workplace safety regulations applicable to the operation of the MCP. These laws and regulations include but are not limited to:

- The Occupational Safety and Health Act
- · Canada Occupational Health and Safety Regulations
- Occupational Safety and Health Acts for Individual States (USA)

For additional information on these regulations as well as industry standards that may apply to this product, please contact:

American National Standards Institute (ANSI) 1430 Broadway New York, NY 10018

New York, NY 10018

Telephone: 212.642.4900

www.ansi.org

Also a member of:

Loading Dock Equipment Manufacturers

A Product Section of Material Handling Industry of America

A Division of Material Handling Industry

8720 Red Oak Blvd, Suite 201

Charlotte, NC, 28217-3992 Telephone: 704.676.1190 www.mhi.org/lodem



2.1 WARRANTY INFORMATION

Thank you for purchasing Blue Giant products. We appreciate your business, and are confident that our product will serve you for many years to come. In the event that you experience a problem with our product, our Warranty Center is here to support the Blue Giant product(s) that you have purchased.

To validate warranty on recently purchased equipment, please complete and submit your information with our Online Warranty Registration at www.BlueGiant.com. For more information about Blue Giant Warranty Support, please contact your local Blue Giant Equipment dealer, representative or authorized partner near you. You may also visit www.BlueGiant.com or phone 1.905.457.3900.

*NOTE that failure to validate warranty at the time of receipt can seriously affect the outcome of any claim.

To validate warranty on recently purchased equipment, please complete and submit your information with our Online Warranty Registration at www.BlueGiant.com. For more information about Blue Giant Warranty Support, please contact your local Blue Giant Equipment dealer, representative or authorized partner near you. You may also visit www.BlueGiant.com or phone 1.905.457.3900.

Dealer Information	
Name:	
Contact:	
Telephone:	

NOTE: Failure to validate warranty at the time of the receipt can seriously affect the outcome of any claim.

2.2 EXCLUSION OF LIABILITY

The manufacturer assumes no liability for damage or injury to persons or property which occur as a result of defects or faults in or incorrect use of the control panel. The manufacturer also assumes no liability for lost profits, operating downtimes, or similar indirect losses incurred by the purchaser. Injury to third parties, irrespective of its nature, is not subject to compensation. The manufacturer reserves the right to make changes at any time to the modules, components, and accessories, concurrent with its continuing product improvements and development program. Specifications, operating instructions, and illustrations included in this manual are subject to change without notice. Please contact manufacturer for the latest information.

2.3 MANUFACTURER'S NOTE

The control panel has been carefully inspected and tested at the manufacturer's plant prior to shipment, but should be checked upon receipt for transport damage. Any observed transport damage is to be listed on the signed copy of the freight document. Notify the freight forwarder of any damage WITHIN 48 HOURS.

2.4 OWNER'S RESPONSIBILITY

- The owner should recognize the inherent danger of the interface between the dock and the freight carrier. The owner should, therefore, train and instruct operators in the safe use of the dock equipment and accessories in accordance with the manufacturer's recommendations.
- 2. The owner should thoroughly familiarize themselves with the following procedures and specifications, and request immediate replacement of all manufacturer-supplied documents that are missing, damaged, or otherwise illegible. Below is a list of Best Practices for dock equipment usage and maintenance.
 - Commissioning instructions
 - Operating instructions
 - · Daily maintenance procedures checklist
 - Inspections procedures
 - Recommended spare parts lists

Upon receipt of any newly purchased dock equipment, the owner shall verify the presence of owner's manuals, operating placards, and any other documentation necessary for training dock personnel how to use the equipment safely and effectively.

- 3. All Blue Giant dock equipment should undergo regularly scheduled planned maintenance. Maintenance requirements will vary according to usage frequency and application, so the owner shall consult with their authorized Blue Giant distributor for schedule recommendation. Written records of the performance of these procedures should be kept as per warranty requirements.
- 4. Dock equipment that is structurally damaged, experiencing performance irregularities, or has been potentially compromised shall be removed from service until a trained and authorized manufacturer's representative can conduct an inspection and perform any necessary repairs.
- 5. As with any piece of machinery, dock equipment requires routine maintenance, lubrication, and adjustments. Recommended procedures are itemized in the Planned Maintenance Program (PMP) checklist included in installation and technical manuals. It is recommended that for anything other than the basic maintenance procedures outlined in this manual, you contact your local Blue Giant representative.
- 6. The owner shall ensure that all name plates and safety labels are in place and legible, and that the appropriate manuals are provided to authorized users. Replacement name plates, safety labels, and manuals are available through the Blue Giant Aftermarket Department. See "Decal Identification and Location" section in this manual for more information.
- 7. The owner or a trained and authorized representative shall verify that all freight carrier brakes have been applied and a vehicle restraint and/or wheel chocks properly engaged before cross-docking procedures begin. For safety reasons trailers must be held securely in place to avoid accidental separation from the loading dock. Unless specifically agreed to in writing by Blue Giant Equipment Corporation at the time of order (and prior to manufacture), all Blue Giant Dock equipment is sold as a complete offering and must not be altered or added to in any manner (which includes configuration and function) without written permission from an authorized manufacturer's representative. These changes shall also satisfy all safety recommendations of the original equipment manufacturer for the particular application of the dock equipment.
- 8. If, at the request of the owner, Blue Giant does not supply all or some of the dock equipment power unit and/or control panel components, the owner shall assume responsibility for any and all operational and safety issues associated with the resulting configuration.

3.0 SAFETY MESSAGE COLOR IDENTIFICATION

This manual includes color-coded safety messages that clarify instructions and specify areas where potential hazard exists. To prevent the possibility of equipment damage and serious injury or death, please observe strictly the instructions and warnings contained in the messages. If warning decals become damaged or missing, replace them immediately. Avoid accidents by recognizing dangerous procedures or situations before they occur.

Danger

Serious injury or death will likely occur if the instructions are not followed.

Warning

Serious injury or death may occur if the instructions are not followed.

Notice

Procedures marked notice must be followed in order to prevent damage to machinery.



Instructions marked caution concern safe operating procedure. Failure to comply may result in personal injury.

3.1 OPERATIONAL SAFETY WARNINGS

Danger

- Do not operate the dock equipment while anyone is standing in its path.
- Lift the dock equipment with suitable hoisting equipment only. Do not stand under the dock equipment or any heavy object while it is being hoisted.
- BEFORE BEGINNING ANY SERVICE PROCEDURES:

Disconnect the power and follow all lockout / tagout procedures outlined in this manual.

Warning

- Installation must be performed only by trained and authorized personnel.
- · Prior to installation, place adequate barriers to prevent vehicle traffic from entering the work area.
- Any electrical work must be performed by qualified personnel only.
- Do not remove the wheel chocks until loading / unloading is finished and the truck is cleared for departure or the vehicle restraint has been released and the lights have changed to RED inside and GREEN outside.

Notice

- Do not ground welding equipment to any electrical components.
- Do not allow the drill to go too deeply into the control box, as damage may occur to the control systems.
- Never use air to blow debris from the control box. Use a vacuum to perform any necessary cleaning.
- Do not connect green ground lead into control box or junction box until all welding has been completed.

A Caution

- Only trained personnel should operate or service this equipment.
- Do not operate the dock equipment until the transport vehicle is parked against the dock bumpers.
- Always park the dock equipment after use (ensure that the lip is safely parked in the lip keepers).
- Conduct routine inspections and maintenance. Failure to do so could cause equipment damage and or personal injury.
- Always call your authorized service representative or manufacturer immediately if a malfunction occurs.
- Always return the restraint arm to the parked position after use.

4.0 LOCKOUT / TAGOUT PROCEDURE AND RULES


Marning

Always lockout and tagout any power source before performing any work on any electrical devices or electrical controls according to OSHA regulations and approved local electrical codes.

In accordance with the rules and regulations of the Occupational Safety and Health Administration (OSHA), all affected employees must be notified that the machine or equipment will be shut down and locked out to perform repair or maintenance work. The work area must be checked to ensure that all personnel have been removed or safely repositioned. The machine or equipment power supply shall be locked in the OFF position or disconnected from the energy source. Blue Giant strongly recommends that only OSHA-approved lockout devices and procedures be utilized.


The energy isolating device must bear a prominent warning tag indicating that work is being done on the equipment and the name of the authorized employee responsible for the lockout. It is mandatory that tagout notices not be susceptible to deterioration or illegibility due to

weather conditions or exposure to chemicals and moisture.



4.1 ROTARY DISCONNECT: PLATINUM SERIES


The Platinum Series has a built-in rotary disconnect. The disconnect has two switch positions: ON and OFF, and can be locked in either position.



5.0 CONTROL PANEL OPERATION: GOLD SERIES III




Controls combinations of all supported dock equipment: one individual vehicle restraint, one individual dock leveler, and controls for a door. Also equipped with touch buttons, inside forklift operator traffic lights, operator menu screen, and keypad for coded features.



NOTE: Typical decal shown, actual decal is bilingual.

5.1 BUTTON FUNCTION: GOLD SERIES III

When touching any of the function buttons or keypad, use the pad of the finger. The control panel's unique touch sensors detect the proximity of the dock operator's finger. Audible touch buttons and keypad on the control panel provide instant sound feedback to user input.



5.2 CONTROL SECTIONS: GOLD SERIES III



This section explains the function of each button on the Gold Series III. General operating instructions for all connected dock equipment appear in the following section.





Menu Screen (LCD Display):

Display digital instructions for the operating and troubleshooting of all connected dock equipment.



FORKLIFT TRAFFIC LIGHTS:

RED: The connection between the dock and trailer is not yet secure.

YELLOW: Caution. Restraint is bypassed or ready to end load when flashing.

GREEN: The connection between the dock and trailer is secure. Also confirms that the leveler is released from home and may be engaged to trailer.



CONTROL PANEL KEYPAD:

Enables code-based security features such as vehicle restraint bypass.



DOOR CONTROL:

OPEN: Opens the overhead door when the door is not programmed to open automatically when the restraint is engaged.

CLOSE: Lowers the overhead door. Must be held.

*If Equipped





RESTRAINT:

ENGAGE: Begins the engagement sequence of the restraint arm / hook.

RELEASE: Disengages the restraint arm / hook.



DOCK LEVELER:

DECK: Raises the deck from the deployed or parked position.

LIP: Deploys the deck lip (also parks the deck lip of vertical storing dock levelers).

DOWN: Lowers the deck (vertical storing dock levelers only) or lowers the Door and Dock Guard via bypass mode (XDS only).

† VL Vertical Storing Dock Leveler and XDS only.



(6)



STOP:

Halts or limits the motion of all interlocked equipment and door.







AUDIBLE SPEAKER:

Brings safety issues to dock attendant's attention.


Emits sound when "Audible touch" buttons are pressed.


6.0 RECOMMENDED SPARE PARTS: GOLD SERIES III














STANDARD OPERATIONAL COMPONENTS								
ITEM	PART NO.	DESCRIPTION	QTY. REQ					
	SINGLE PHASE							
	026-PB1115	Power Board Sub-assembly (1PH 115V 50-60HZ)	1					
	026-PB1230	Power Board Sub-assembly (1PH 230V 50-60HZ)	'					
	THREE PHASE							
1	026-PB3230	Power Board Sub-assembly (3PH 230V 50-60HZ)						
	026-PB3400	Power Board Sub-assembly (3PH 400V 50-60HZ)						
	026-PB3460	Power Board Sub-assembly (3PH 460V 50-60HZ)	1					
	026-PB3575	Power Board Sub-assembly (3PH 575V 50-60HZ)						
	026-G021-99	Control/Touch Board w/LED and LCD Modules	1					
2	BGG2xxEx-TC	Transparent Cover Door	1					
	_	Decal, Part # based on Serial #	1					
3	026-G025M	Remote I/O-A Board w/ Resistor	1					
4	026-G025BM	Remote I/O-B Board w/o Resistor (For SVR303)	1					
5	026-G025-99M	Remote I/O-B Board w/ Door Control	1					
6	026-G030	Ribbon Cable, 16 Wire/Pin w/ Connector	1					
	026-G100	Fuse, 15A, 250V, Slow Blow for 1PH, 110-130V	1					
7	026-G101	Fuse, 8A, 250V, Slow Blow for 1PH, 208-240V	1					
	026-G102	Fuse, 0.5A, 250V, Slow Blow for 1 and 3PH, 208-240V	1					

STANDARD OPERATIONAL COMPONENTS							
ITEM	PART NO.	DESCRIPTION	QTY. REQ				
	026-G103	Fuse, 0.25A, 250V Slow Blow for 1PH, 208-240V	1				
	026-G104	Fuse, 0.75A, 250V Slow Blow for 1PH, 110-130V	1				
	026-G105	Fuse, 500mA, 700V, Fast Blow for 3PH, 380-415V	1				
	026-G106	Fuse, 400mA, 700V, Fast Blow for 3PH, 440-480V	1				
	026-G107	Fuse, 315mA, 700V, Fast Blow for 3PH, 575-600V	1				
	026-G123	Fuse, 5A, 250V, Slow Blow for 1PH, 110-130V	1				
	026-G100	Fuse, 15A, 250V, Slow Blow for 1PH, 110-130V	1				
7	026-G101	Fuse, 8A, 250V, Slow Blow for 1PH, 208-240V	1				
	026-G102	Fuse, 0.5A, 250V, Slow Blow for 1 and 3PH, 208-240V	1				
	026-G103	Fuse, 0.25A, 250V, Slow Blow for 1PH, 208-240V	1				
	026-G104	Fuse, 0.75A, 250V, Slow Blow for 1PH, 110-130V	1				
	026-G105	Fuse, 500mA, 700V, Fast Blow for 3PH, 380-415V	1				
	026-G106	Fuse, 400mA, 700V, Fast Blow for 3PH, 440-480V	1				
	026-G107	Fuse, 315mA, 700V, Fast Blow for 3PH, 575-600V	1				
	026-G123	Fuse, 5A, 250V, Slow Blow for 1PH, 110-130V	1				
*Optio	nal † If Equipped						


7.0 EQUIPMENT COMPONENT ILLUSTRATIONS: GOLD SERIES III





Item	Qty	Part NO.		Description	Approx	Weight
1	1	Dependent on voltage See Section 7.2		Blue Genius™ Gold Series III Control Panel	10 lb	4.5 kg
2	1	025-G010-1		Mounting Tabs with hardware (1 pkg. of 4)	_	_
			Е			
0	1	000 005	F	Fishering Driver Meminer Cine	0.7 lb	0.32 kg
3	'	038-225	S	Exterior Driver Warning Sign		
			Р			
4	1	032-806		Exterior Driver Traffic Light	1.3 lb	0.6 kg
		1 038-918	Е			
5	1		F	Owner's Manual	_	_
			S			
			Е			
6	1	Dependent on model #	F	Operation Placard(s)	_	_
		S				

7.2 MECHANICAL ASSEMBLY: GOLD SERIES III



COMPLETE CONTROL STATION ASSEMBLY - ITEM 1 (Example BGGFS1115F)										
ITEM	SINGLE PHASE									
	◊	FUSE	QTY	PART NO.	DESCRIPTION	ASSY PART#	*			
	F1	A J	1	026-PB1115	Power Poord Cub Assembly + (1PH 115)/ 50 60H7)	BGGFS1115	F			
	F2	E	1	020-PB1115	Power Board Sub-Assembly † (1PH 115V 50-60HZ)	BGGFS1115	S			
	F1	С	1	026-PB1230	Power Board Sub-Assembly † (1PH 115V 50-60HZ)	BGGFS1230	F			
	F2		1	020-FB1230	Fower board Sub-Assembly (TFTT 113V 30-00112)	BGGF31230	S			
	THREE PHASE									
	♦	FUSE	QTY	PART NO.	DESCRIPTION	ASSY PART#	*			
2	F1	C 1	1	026-PB3230	Power Board Sub-Assembly † (3PH 230V 50-60HZ)	BGGFS3230	F			
	F2		1	020-1 00200	Tower Board Sub-Assembly (GITT 2507 50-00112)	Bddi 30200	S			
	F1	F	1	026-PB3400	Power Board Sub-Assembly † (3PH 400V 50-60HZ)	BGGFS3400	F			
	F2	'	1		Tower Board Cab Assembly (Criti 400 V Co Coriz)	Baar 00400	S			
	F1	G	1	026-PB3460	Power Board Sub-Assembly † (3PH 460V 50-60HZ)	BGGFS3460	F			
	F2		1	020 1 20400	1 3 1 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	244, 20400	S			
	F1	Н	1	026-PB3575	Power Board Sub-Assembly † (3PH 575V 60HZ)	BGGFS3575	F			
	F2		1	026-2835/5	Tower board oub-Assembly (of 11373V 00112)	20010	S			


ITEM	QTY	PART NO.		DESCRIPTION
3	1	025-G010-M		Control Box Enclosure (Includes 4C)
4	1	025-G014-V3	B-M	Transparent Cover Door (4C) and Touch Control Board(4A) (Serial # Required)
4A	1	026-G021-M		Touch Control Board (Serial # Required)
4B	5	025-062		Cable Tie Mount
4C	1	025-G014		Transparent Cover Door
5	1	038-XXXE	F	Face Decal (Dependent on Configuration)
Э	'	030-XXXE	S	(Not sold separately)
6	1	025-G010-1		Mounting Tabs with Hardware (1 pkg. of 4)
7	1	026-G030		Ribbon Cable
	_	038-284E	F	Decel Cariel Dieta (Net cold concretely)
8	1		S	Decal, Serial Plate (Not sold separately)
9	1	038-283ESF		Decal, Do Not Drill
10	_	038-853E	F	Warning Dood
10	10 1	030-033E	S	Warning Decal
11	1	026-615-1		Anti-Static Poly Bag (Wiring Diagram Enclosed) (Serial # required for diagram)
12	1	026-G402-B		Audible Speaker
F3	1	026-037-1		Fuse, 2.5A, 700V, Fast Blow 1/4" Glass


^{*} Language on decal: F = English / French S = English / Spanish \Diamond Location on Power Board † Includes Fuses ‡ 115 Volt Control Box Shown

AS PE	AS PER VOLTAGE - SEE ITEM 11							
ITEM	QTY	PART NO.	DESCRIPTION	USE				
Α	1	026-G100	Fuse, 15A, 250V for 1PH,110-130V	LEVELER, SVR303				
В	1	026-G101	Fuse, 8A, 250V for 1PH, 208-240V	TL85				
С	1	026-G102	Fuse, 0.5A, 250V for 1 and 3PH, 208-240V					
D	1	026-G103	Fuse, 0.25A, 250V for 1PH, 208-240V					
Е	1	026-G104	Fuse, 0.75A, 250V, for 1PH, 110-130V					
F	1	026-G105	Fuse, 500mA, 700V for 3PH, 380-415V					
G	1	026-G106	Fuse, 400mA, 700V for 3PH, 440-480V					
Н	1	026-G107	Fuse, 315mA, 700V for 3PH, 575-600V					
J	1	026-G123	Fuse, 5A, 250V for 1PH 110-130V	HVR303				

7.3 GENERAL DIMENSIONS: GOLD SERIES III








8.0 CONTROL PANEL OPERATION: PLATINUM SERIES


Controls combinations of all supported dock equipment: one individual vehicle restraint, dock leveler, door, inflatable seal, and dock light. Also equipped with touch buttons, inside forklift operator traffic lights, operator menu screen, and keypad for coded features.



NOTE: Typical decal shown, actual decal is bilingual.

8.1 BUTTON FUNCTION: PLATINUM SERIES

When touching any of the function buttons or keypad, use the pad of the finger. The control panel's unique touch sensors detect the proximity of the dock operator's finger. Audible touch buttons and keypad on the control panel provide instant sound feedback to user input.



8.2 CONTROL SECTIONS: PLATINUM SERIES

This section explains the function of each button on the Platinum Series. General operating instructions for all connected dock equipment appear in the following section.





MENU SCREEN (LCD DISPLAY):

Displays digital instructions for the operating and troubleshooting of all connected dock equipment.





LANGUAGE:

Changes the LCD display language to English, French, or Spanish.





LED CONTROL PANEL LIGHTS:

RED: Do Not Enter: the connection between the dock and trailer is not yet secure. YELLOW: Caution. Restraint is bypassed or ready to end load when flashing.

GREEN: Enter: the connection between the dock and trailer is secure.






CONTROL STATION KEYPAD:

Enables code-based security features such as vehicle restraint bypass.





ROTARY DISCONNECT:

ON: Locks the control panel enclosure and provides power to the unit. **OFF:** Unlocks the control panel enclosure and cuts power to the unit.





RESTRAINT:

ENGAGE: Begins the engagement sequence of the restraint arm / hook.

RELEASE: Disengages the restraint arm / hook.





INFLATABLE SEAL:

Activates and deactivates the inflatable seal when the seal is not in automatic mode.



DOCK LEVELER:

DECK: Raises the deck from the deployed or parked position.

LIP: Deploys the deck lip (also parks the deck lip of vertical storing dock levelers).

DOWN: Lowers the deck (vertical storing dock levelers only) or lowers the Door and Dock

Guard via bypass mode (XDS only).



DOCK LIGHT:

Activates and deactivates the dock light when the light is not in automatic mode.



DOOR:

OPEN: Opens the overhead door when the door is not programmed to open automatically when the restraint is engaged.


CLOSE: Lowers the overhead door. Must be held.

STOP: Stops the door in mid-motion.



STOP:

Halts or limits the motion of all interlocked equipment and door.




AUDIBLE SPEAKER:


Brings safety issues to dock attendant's attention.


Emits sound when "Audible touch" buttons are pressed.


9.0 RECOMMENDED SPARE PARTS: PLATINUM SERIES






















STANDARD OPERATIONAL COMPONENTS							
ITEM	PART NO. DESCRIPTION		QTY. REQ				
1	026-CB-BGP-1	Control Board Assembly	1				
2	026-XXXXXX-BGP	Relay Board Assembly See Section 10.2	1				
3	026-PBXXX-BGP	Power Board Assembly See Section 10.2	1				
4	026-IO-BGP	PCB, BGP, I/O	1				
5*	028-588	Disconnect Switch	1				
6*	028-586	Receptacle GFI	1				
7	028-605	4 A Circuit Breaker (Shown)	1				
1	026-746	15 A Circuit Breaker	1				
8	See Section 10.2	15 A Circuit Breaker	_				
9	See Section 10.2	Fuse Control	_				
10	026-G030	Ribbon Cable (16C)	1				
9	See Section 10.2 026-G030	Fuse Control					


10.0 EQUIPMENT COMPONENT ILLUSTRATIONS: PLATINUM SERIES

10.1 COMPONENTS AS SHIPPED CHECK LIST: PLATINUM SERIES



Item	Qty	Part NO.		Description	Approx. Weight	
1	1	BGP-4-XXXXX-X Dependent on voltage See Section 10.2		Blue Genius™ Platinum Series Control Panel	25 - 35 lb	11 - 16 kg
2	1	025-G012-1		Mounting Tabs with hardware (1 pkg. of 4)	_	_
			Е			
0		038-225	F	Futorior Driver Meminer Cine	0.7 lb	0.32 kg
3	1		S	Exterior Driver Warning Sign		
			Р			
4	1	032-806		Exterior Driver Traffic Light	1.3 lb	0.6 kg
-		038-918	E	Owner's Manual		
5	1		F		_	_
			S			
			Е			
6	1	Dependent on model #	F	Operation Placard(s)	_	_
		S				

10.2 MECHANICAL ASSEMBLY: PLATINUM SERIES



	T .	T	1		TEM 1 (Example BGGFS1115F)		一				
ITEM	\Q	FUSE		PART NO.	DESCRIPTION	ASSY PART#	*				
	SINGI	_E PHAS	E - PO\	WER BOARD							
	F1	В	2	026-PB1115-BGP	Power Board † Assembly, 115V, 1PH	BGP-4-115	F				
	F2 F3	С	3	920 1 2 1 1 1 0 2 0		26.1	5				
	F4	D	2	026-PB1230-BGP	Power Board † Assembly, 230V, 1PH	BGP-4-230-115	F				
	F5	С	3		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,						
	THRE	T		/ER BOARD							
		D	2	026-PB230-BGP	Power Board † Assembly, 230V, 3PH	BGP-4-230-115	F				
		С	3								
		F	2			BGP-4-460-115	H				
2				026-PB400-BGP	Power Board † Assembly, 400V, 3PH						
		С	3			BGP-4-460-230	H				
	F1 F2						1				
	F3	G	2			BGP-4-460-115	Н				
	F4 F5			026-PB460-BGP	Power Board † Assembly, 460V, 3PH		ŀ				
		С	3			BGP-4-460-230	Н				
		E	2		Power Board † Assembly, 575V, 3PH	BGP-4-575-115	ŀ				
				026-PB575-BGP							
		С	3			BGP-4-575-230	Ь				
	SING	E PHAS	F - RFI	AY BOARD			L				
	F20						Т				
	F21	1.1 14	4	026-RB1230-BGP	Relay Board Assembly, 115-220V, 1PH	BGP-4-115	L				
	F22 F23				<i>,</i> ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,						
	THREE PHASE - RELAY BOARD										
							Ī				
				026-RB3230-BGP	Relay Board Assembly 220V, 3PH	BGP-4-230-115	ľ				
3						DOD 4 400 445					
	F00							BGP-4-460-115			
	F20 F21					DCD 4 460 000					
	F22	2 J	4	006 BB2575 BCB	Polov Poord Accombly 400 575V 2DL	BGP-4-460-230					
	F23								026-RB3575-BGP	Relay Board Assembly 400-575V, 3PH	BGP-4-575-115
						BGF-4-375-115					
						BGP-4-575-230					
						BGF-4-375-230					
				026-381	Transformer, 1000VA, 240V-120V	BGP-4-230-115					
				026-380	Transformer, 1000VA, 480V-120V	BGP-4-460-115					
				026-382	Transformer, 1000VA, 480V-240V	BGP-4-460-230					
				026-383	Transformer, 1000VA, 600V-120V	BGP-4-575-115					
			1	026-384	Transformer, 1000VA, 600V-240V	BGP-4-575-230					
					Transformer, 2000VA, 480V - 120V	BGP-4-460-115					
				026-385	Transformer, 2000VA, 480V - 240V	BGP-4-460-230					
	ı				320 000	Transformer, 2000VA, 600V - 120V	BGP-4-575-115				


^{*} Language on Decal: F = English / French, S = English/Spanish \Diamond Location on Power Board, † Includes Fuses

ITEM	QTY	PART NO.		DESCRIPTION
5	1	025-G012-A		Enclosure
6	1	025-G030-A		Assembly, Plate, Backing
7		025-G035		Assembly, DIN Rail, BGP (4A)
7	1	025-G036		Assembly, DIN Rail, BGP (15A)
8	1	028-592		Shaft, Disconnect
9	1	025-G031-A		Divider Plate
10	1	038-400E F		Decal, Blue Genius™ Platinum Series *(Not sold separately)
11	1	028-590		Rotary Disconnect Handle
12	1	026-IO-BGP		PCB, BGP. I/O
13	1	026-CB-BGP-1		Control Board Assembly
14	1	028-586		GFI Receptacle 120V (4A STD. 15A OPT.)
15	1	028-587		Receptacle Cover
16	1	026-G030		Ribbon Cable
17	1	026-G402-B		Audible Speaker
18	4	025-G012-1		Mounting Tabs
19	1	026-G048-A		Cable Assembly, BGP, I/O-RLY, 28.5," 8Pins
20	1	026-G049-A		Cable Assembly, BGP, PSU-I/O, 13.5," 10Pins
21	1	038-283ESF		Decal, Do Not Drill
22	1	038-853E F		Warning Decal *
23	1	026-615-1		Anti-Static Poly Bag (Wiring Diagram Enclosed - Serial # req'd for diagram)
24	1	038-284E F		Decal, Serial Plate *
25	2	025-G032		Hinge Kit, DSE Control Box
26	1	030-907		Enclosure Frame, BGP
27	1	026-G228		Stop Push Button Control (Optional)

^{*} Language on Decal: F = English / French, S = English/Spanish

AS PE	AS PER VOLTAGE - SEE ITEM 11							
ITEM	QTY	PART NO.	DESCRIPTION	USE				
В	1	026-G101	Fuse, 8A, 250V for 1PH, 208-240V	TL85				
С	1	026-G102	Fuse, 0.5A, 250V for 1 and 3PH, 208-240V					
D	1	026-237-1	Fuse, 2.5A, 250V, Fast Blow					
Е	1	026-G104	Fuse, 0.75A, 250V, for 1PH, 110-130V					
F	1	026-G105-SB	Fuse, 500mA, 700V for 3PH, 380-415V					
G	1	026-G106	Fuse, 400mA, 700V for 3PH, 440-480V					
Н	1	026-G107	Fuse, 315mA, 700V for 3PH, 575-600V					
J	1	026-G123	Fuse, 5A, 250V for 1PH 110-130V	HVR303				
J	1	026-G123	Fuse, 5A, 250V for 1PH 110-130V	HVR303				

10.3 GENERAL DIMENSIONS: PLATINUM SERIES



11.0 DECAL IDENTIFICATION AND LOCATION: GOLD SERIES III AND PLATINUM SERIES



ITEM	QTY	PART NO.	*	DESCRIPTION	
1	1	028-587	F/S	Decal - Do Not Drill	
2	1	038-853E	F/S	Decal - Warning	
3	1	038-285E	F/S	Decal - Serial Plate (Not sold separately) (Located inside control box enclosure)	
4	1	038-296E	F/S	Decal - Warning Interior Control Box	
5	1	Dependent on Model	F/S	Decal - Blue Genius Gold Series III (Not sold separately)	
6	1	038-400E	F/S	Decal - Blue Genius Platinum Series (Not sold separately)	
* Language on Decal: F = English / French. S = English/Spanish					

12.0 STOP PROCEDURE: GOLD SERIES III AND PLATINUM SERIES




If dock equipment needs to be stopped immediately, the operator can use the 'STOP' button. Touching the 'STOP' button during operation allows the operator to halt or limit equipment motion in the event of a potential emergency.

When in STOP mode:


- DO NOT go under the dock leveler
- DO NOT walk or drive on lip or deck
- · DO NOT leave truck or material sitting on the leveler
- 1) Touch the 'STOP' button. The control panel light instantly changes to flashing RED and the exterior traffic light will turn RED. The audible alarm will beep until stop mode is exited.

To silence the audible alarm, touch the 'STOP' button a second time as acknowledgment that stop has been activated.




2) "SYSTEM STOPPED, To Continue...Touch and Hold ESC Key" will appear on LCD screen.

Verify surroundings and corrections before exiting stop mode.



3) To exit stop mode, touch the 'ESC' button. "Please Wait..." will appear on LCD screen.

The system will reset with lights and operation as required.




13.0 OPERATING INSTRUCTIONS: GOLD SERIES III AND PLATINUM SERIES


Operating instructions are not always chronological. Perform steps as necessary. The following steps apply to pit-style dock levelers only.




Before the truck enters the driveway, the exterior traffic light will be GREEN and the control panel light will be RED. The screen will read "Blue Genius Ready." The truck may now enter the driveway. This sequence also indicates that it is safe for the truck to leave at the end of loading / unloading.




Touch the 'Engage' button to activate vehicle restraint. Exterior traffic light will change to RED. Screen will read "Restraint Engaging." Once the ICC bar is secured, the message will change to "Restraint is Engaged" followed by "Dock Leveler Restored" and "Ready to Raise Deck." If a warning message appears on the screen, see Section "14.0 ENGAGING THE OVERRIDE FEATURE: Gold Series III and Platinum Series" on page 32




Press the 'OPEN' button to raise the overhead door when the door is not in automatic mode. Screen will read "Door is Opening."




Touch the 'Deck' button. Screen will read "Deck Raising." Hold until lip deploys. Release button. Screen will read "Deck Moving." Dock leveler and lip will descend onto the truck bed. Screen will read "Deck Deployed." Control panel light will turn GREEN. If deploying below level, see Section "13.1 ALTERNATIVE METHODS OF OPERATION: Gold Series III AND Platinum Series" on page 31.



Touch and hold the 'Deck' button. Screen will read "Deck Raising." When the lip has cleared the lip keepers or trailer, release the "Deck" button and touch and hold the 'Lip' button. Screen will read "Lip Moving." Release button. Screen reads "Deck Moving." The leveler and lip will descend to truck bed, message will change to "Deck Deployed" Control panel light will turn GREEN.



Restraint and leveler deployed correctly. Perform loading and unloading.




PERFORM LOADING AND UNLOADING


Touch and hold the 'Deck' button. Control panel light will turn RED. The deck will raise and lip will retract. When the lip has fully retracted, release the 'Deck' button. Screen will read "Deck Moving" and the deck will lower to stored position with the lip in the lip keepers. Message will change to "Dock Leveler Restored" followed by "Ready to Release" (refers to vehicle restraint).

NOTE: Following this step, press the 'Close' button on the door controls (see Section "13.0 OPERATING INSTRUCTIONS: Gold Series III AND Platinum Series" on page 29, Step C) to lower the overhead door. Screen will read "Door is Closing."

Touch the 'Release' button. Screen will read "Restraint Releasing." When the restraint is in the home position, message will change to "Blue Genius Ready."

*Traffic light will turn GREEN after the restraint is lowered.







13.1 ALTERNATIVE METHODS OF OPERATION: GOLD SERIES III AND PLATINUM SERIES



Touch the 'Deck' button. Screen will read "Deck Raising." Hold until lip partially extends. Release 'Deck' button. Screen will read "Deck Moving." The dock leveler and lip will descend. The lip will hang in pendent position between dock face and trailer. Screen will read "Deck Deployed." Control panel light will turn GREEN.



Touch and hold the 'Deck' button until the dock is high enough for the lip to deploy safely onto the load bed. Return to Step F of Section "13.0 OPERATING INSTRUCTIONS: Gold Series III AND Platinum Series" on page 29.




14.0 ENGAGING THE OVERRIDE FEATURE: GOLD SERIES III AND PLATINUM SERIES

Should it be necessary to bypass the vehicle restraint function (i.e. the truck has an outdated, damaged, or missing ICC bar), a system-approved override code may be entered via the Blue Genius™ touch keypad. This code can be used whether or not the dock leveler is interlocked with the Blue Genius™. Ensure that the vehicle is manually chocked before loading and unloading begins.


NOTE: If a visual inspection confirms that the ICC bar is missing or too damaged to be secured then depending on your Blue Genius Software version:

- Up to Version 3.0 (inclusive), bypass Step 1 in the instructions below and go directly to Step 2, which explains how to enter the Override Code.
- From Version 3.1 and higher, step 1 is required sequence and then proceed to step 2, follow the instructions. Alternative sequence processes may be available, please consult your Blue Giant representative.
- During "Engaging the Vehicle Restraint" (see Section "13.0 OPERATING INSTRUCTIONS: Gold Series III AND
 Platinum Series" on page 29, Step B), the LCD screen may
 read "ICC Bar Not in Range." This message indicates that a
 vehicle's ICC bar is absent or cannot be engaged. Determine
 whether the vehicle needs to be realigned or if wheel chocks are
 necessary. Press "SEL" to continue.




a. Press the * key on the keypad. The LCD screen will read 'Enter Code *___'.
Enter the supervisor code (default factory set code is '247').

NOTE: The default code can be changed. Please call your Blue Giant representative for further information.




Continue operation of overhead door, dock leveler, and vehicle restraint as outlined in Sections "13.0 OPERATING INSTRUCTIONS: Gold Series III AND Platinum Series" on page 29, and "13.1 ALTERNATIVE METHODS OF OPERATION: Gold Series III AND *Platinum Series"* on page 31. The following indicators will appear:

b. The LCD screen will read 'Dock Leveler Restored' and then "Ready to Deploy Deck," followed by "Restraint Is Bypassed."



c. Once the deck is deployed and the home sensor becomes inactive, the control panel light will turn GREEN while flashing YELLOW. This indicates that the vehicle restraint is not engaged.



14.1 RELEASING THE OVERRIDE FEATURE: GOLD SERIES III AND PLATINUM SERIES




Store the dock leveler.

NOTE: Override is still active when dock leveler and vehicle restraint are in the parked position.

The control panel light will turn RED.


Touch the 'Release' button on the control panel to release the override. The control panel will verify that the vehicle restraint has been lowered to the home position. The LCD screen will read "Blue Genius Ready" (see Section "13.0 OPERATING INSTRUCTIONS: Gold Series III AND Platinum Series" on page 29, Step H)

The exterior traffic light will turn GREEN, advising the truck driver that it is safe to depart once the wheel chocks are removed.



15.0 EXTERIOR TRAFFIC LIGHT / MIRROR SIGN IMAGE: GOLD SERIES III AND PLATINUM SERIES

The LED traffic lights and mirror image drive warning sign improve loading dock safety.



NOTE: Mount to a flat surface. DO NOT deform light housing with irregular wall surface.

16.0 CONTROL PANEL LCD MESSAGES: GOLD SERIES III AND PLATINUM SERIES



MARNING

Do not attempt to install, make repairs or adjustments. Only a trained and authorized service technician should perform the installation process. Contact your local dealer or distributor for assistance.

MESSAGE	EXPLANATION				
'Fault 31' IPS sensor value too low	 IPS shaft not secured by set screw, tighten set screw making sure the IPS green LED light is lit with the restraint arm in its lowered position. NOTE: the set screw does not tighten down on the flat of the IPS shaft. IPS not programmed. See set-up procedure. 				
During self test mode the following message appear: 'Remote I/O Bad' 'Positioner Bad'	Faulty wiring, communication cable not connected or damaged. Circuit board faulty.				
'Please restore Dock Leveler'	 Restraint interlock sensor (home/lip) is in-active, out of range. Restraint interlock sensor (home/lip) is not connected. Faulty wiring. Dock not in stored/home position. 				
'ICC Bar not in Range'	 Restraint arm went up and did not find ICC bar in preset range. IPS not programmed. 				
'Fault 10' Communication error	 Faulty wiring, check for loose or broken communication cable wire(s). Noise interference, check routing of communication from Blue Genius™ controls to remote devices. 				
'Restraint Arm Blocked' Followed by: 'Restore Restraint, press 'SEL' to continue, Blue Genius™ Warning' (repeats)	 Restraint arm failed to lower all the way down. Check for debris. Faulty IPS board or switches. Faulty wiring. 				
'Restraint is Engaged' Followed by: 'Dock Leveler Restored', 'Ready to Deploy Deck'. (repeats)	The 'Engage' button has been touched and vehicle restraint is in locked position.				
During self test mode the following message appears: 'Remote I/O Bad'	 Faulty wiring, check communication cable wires for loose connections. Remote I/O is faulty, replace. Blue Genius[™] power board is faulty, replace. 				
During self test mode the following message appears: 'Positioner Bad'	 Faulty wiring, check communication cable wires for loose connections. IPS board is faulty, replace. Blue Genius™ power board is faulty, replace. 				
'Restraint fault - COMB - Main power'	1. Change F3. Not F1.				


17.0 WIRING DIAGRAMS: GOLD SERIES III AND PLATINUM SERIES




NOTICE

The following wiring diagrams are sample configurations only. Wiring diagrams specific to your needs will be provided inside the control panel and/or as part of your submittal package.


17.1 WIRING DIAGRAM—115V SINGLE PHASE: GOLD SERIES III (SVR303 & FH COMBO)




17.2 WIRING DIAGRAM—230V SINGLE PHASE: GOLD SERIES III (TL85 REMOTE & FH COMBO)




17.3 POWER WIRING DIAGRAM - 230-575V THREE PHASE: PLATINUM SERIES* (SVR303 & VL COMBO)






^{*}For 230/400/460/575V 3PH 50-60HZ input power.

17.4 CONTROL WIRING DIAGRAM - 230-575V THREE PHASE:PLATINUM SERIES (SVR303 & VL COMBO)





BLUE GENIUS™	TOUCH CONTROL M	IASTER CONTROL PA	NELS — OWNER'S	MANUAL	

BLUE GENIUS™ TOUCH CONTROL	MASTER CONTROL F	PANELS — OWNER'S	S MANUAL

